RAYNOR GARAGE DOORS

Raynor EnergyCore

Polystyrene Insulated Sectional Door

The Raynor EnergyCore Series opens a world of opportunity and color for commercial applications at a competitive price point. Engineered for durability and energy savings, this steel two-sided door has 2" thick polystyrene insulation and is available in either 26 gauge (EC200) or 24 gauge (EC224) exterior steel. Available in a variety of colors and styles, Raynor EnergyCore is the perfect solution for many commercial applications.

EC200
The EC200 features a 26-gauge steel exterior with a laminated core of expanded polystyrene insulation. EC200 is offered with a number of exterior color selections and optional windows to meet the need of any application.

EC224
The EC224 boasts a 24-gauge exterior steel option and is available in white. EC224 is perfect for applications where thicker steel is specified.

Raynor EnergyCore

Section Details

	EC200	EC224
Max. Door Width	24'-2"	24'-2"
Max. Door Height	16'-0"	16'-0"
Construction	Steel Sandwich	Steel Sandwich
Surface Texture	Gunite	Gunite
Section Thickness	2"	2"
Exterior/Interior Steel Thickness	26 Gauge/ 26 Gauge	24 Gauge/ 26 Gauge
End Stile Steel Thickness	18 Gauge	18 Gauge
Insulation (R-Value*)	Expanded Polystyrene (10.0)	Expanded Polystyrene (10.0)
Standard Exterior Colors	White, Taupe, Brown	White
Optional Exterior Colors	Shale, Grey, Black	

Additional Features

Track, Springs & Hardware	Raynor EnergyCore Series doors come packaged with the right combination of track, springs and hardware to precisely match your door's size and application. A QuikClip™ pre-assembled track option is also available.
WeatherLock™	Arctic grade bottom weatherseal keeps out the elements.
QuickDock™	A QuickDock option offers preassembled, palletized sections for safer, faster and easier installation on orders of 36 doors or more.
ControlHoist™	Raynor has a full line of commercial operators for your door. Extended 3 year warranty when purchased with a Raynor door.

Follow Us

Finishes & Glazing Options

Panels

Flush | Pencil Groove

Finish

Gunite Surface Texture

Glazing

Raynor EnergyCore windows use 1/8" insulated glass

24"x8" | 24"x12" | 34"x16" | FullView

Limited Warranty†

Sections	10 - Years Rust-through and Delamination
Track, Springs & Hardware	1 - Year

*R-VALUE: Pending testing in accordance with DASMA TDS-163

†LIMITED WARRANTY: See your local Raynor Authorized Dealer for complete details.

©2023 Raynor
2910051 03/24